

Oil-/fuel separator for underground installation

Oil-/fuel separator according to KESSEL Standard

NS 1.5

Illustration and dimensioned drawing	Article description	Ø	Weight	Article #																																
	<p>Oil-/fuel separator NS 1.5, class II, Ø 1000 For underground installation, installation depth D = mm</p> <p>With integrated sludge trap and self-actuated closure lock, calibrated for light liquid with densities between 0.85 to 0.95 g/cm³.</p> <p>Optional with backwater flap valve according to DIN 13564</p> <p>Upper sections made of polymer, continuous height and level adjustment, cover class D. Inlet and outlet Ø 110 for synthetic material pipes in: PE-HD (according to EN 12666-1); PVC pipe (according to EN 1401-1); PP or AS.</p> <p>Accessories: - Sampling chamber - Alarm unit (upon request); not suitable for <i>SonicControl</i></p>	1000	110 kg	99 601.041D																																
	<table border="1"> <thead> <tr> <th>NS</th> <th>Ø</th> <th>Sludge trap capacity</th> <th>L</th> <th>B</th> <th colspan="2">D</th> <th>h2</th> <th>h1</th> <th>Oil storage capacity</th> <th>Excess level</th> </tr> <tr> <th></th> <th></th> <th></th> <th></th> <th></th> <th>min</th> <th>max</th> <th></th> <th></th> <th></th> <th></th> </tr> </thead> <tbody> <tr> <td>NS 1.5</td> <td>110</td> <td>360 l</td> <td>1425</td> <td>1300</td> <td>570</td> <td>995</td> <td>630</td> <td>583</td> <td>110 l</td> <td>70</td> </tr> </tbody> </table>	NS	Ø	Sludge trap capacity	L	B	D		h2	h1	Oil storage capacity	Excess level						min	max					NS 1.5	110	360 l	1425	1300	570	995	630	583	110 l	70		
NS	Ø	Sludge trap capacity	L	B	D		h2	h1	Oil storage capacity	Excess level																										
					min	max																														
NS 1.5	110	360 l	1425	1300	570	995	630	583	110 l	70																										
	<p>Oil-/fuel separator NS 1.5, class II, Ø 800 For underground installation, installation depth D = mm</p> <p>With integrated sludge trap and self-actuated closure lock, calibrated for light liquid with densities between 0.85 to 0.95 g/cm³.</p> <p>Optional with backwater flap valve according to DIN 13564</p> <p>Upper sections made of polymer, continuous height and level adjustment, cover class B/D. Inlet and outlet Ø 110 for synthetic material pipes in: PE-HD (according to EN 12666-1); PVC pipe (according to EN 1401-1); PP or AS.</p> <p>Accessories: - Sampling chamber - Alarm unit (upon request); not suitable for <i>SonicControl</i></p>	800 800	74 kg 74 kg	99 601.016B 99 601.016D																																
	<table border="1"> <thead> <tr> <th>NS</th> <th>Ø</th> <th>Sludge trap capacity</th> <th>L</th> <th>B</th> <th colspan="2">D</th> <th>h2</th> <th>h1</th> <th>Oil storage capacity</th> <th>Excess level</th> </tr> <tr> <th></th> <th></th> <th></th> <th></th> <th></th> <th>min</th> <th>max</th> <th></th> <th></th> <th></th> <th></th> </tr> </thead> <tbody> <tr> <td>NS 1.5</td> <td>110</td> <td>130 l</td> <td>1091</td> <td>1012</td> <td>518</td> <td>942</td> <td>508</td> <td>461</td> <td>70.5 l</td> <td>50</td> </tr> </tbody> </table>	NS	Ø	Sludge trap capacity	L	B	D		h2	h1	Oil storage capacity	Excess level						min	max					NS 1.5	110	130 l	1091	1012	518	942	508	461	70.5 l	50		
NS	Ø	Sludge trap capacity	L	B	D		h2	h1	Oil storage capacity	Excess level																										
					min	max																														
NS 1.5	110	130 l	1091	1012	518	942	508	461	70.5 l	50																										
	<p>Oil-/fuel separator NS 1.5, class II, Ø 400 For underground installation, installation depth D = mm</p> <p>With integrated sludge trap and self-actuated closure lock, calibrated for light liquid with densities between 0.85 to 0.95 g/cm³.</p> <p>Optional with backwater flap valve according to DIN 13564</p> <p>Upper sections made of polymer, continuous height and level adjustment, cover class B. Inlet and outlet Ø 110 for synthetic material pipes in: PE-HD (according to EN 12666-1); PVC pipe (according to EN 1401-1); PP or AS.</p> <p>Accessories: - Sampling chamber - Not suitable for <i>SonicControl</i></p>	400	12 kg	99 601.002B																																
	<table border="1"> <thead> <tr> <th>NS</th> <th>Ø</th> <th>Sludge trap capacity</th> <th>L</th> <th>B</th> <th colspan="2">D</th> <th>h2</th> <th>h1</th> <th>Oil storage capacity</th> <th>Excess level</th> </tr> <tr> <th></th> <th></th> <th></th> <th></th> <th></th> <th>min</th> <th>max</th> <th></th> <th></th> <th></th> <th></th> </tr> </thead> <tbody> <tr> <td>NS 1.5</td> <td>110</td> <td>17 l</td> <td>582</td> <td>520</td> <td>231</td> <td>324</td> <td>389</td> <td>342</td> <td>17.6 l</td> <td>50</td> </tr> </tbody> </table>	NS	Ø	Sludge trap capacity	L	B	D		h2	h1	Oil storage capacity	Excess level						min	max					NS 1.5	110	17 l	582	520	231	324	389	342	17.6 l	50		
NS	Ø	Sludge trap capacity	L	B	D		h2	h1	Oil storage capacity	Excess level																										
					min	max																														
NS 1.5	110	17 l	582	520	231	324	389	342	17.6 l	50																										